

Fit for any transport and carriage need, **Truck Travel** is the ideal solution for local authorities and companies in need of economical and convenient



<b>Vehicle category</b>	Chassis N1 – Rear driving axle
<b>Cab seats</b>	2
<b>Engine</b>	Central longitudinal electric, DC, 84v-10kv rated - 18 kv max.
<b>Speed gear</b>	1-speed
<b>Inverter</b>	MOSFET with energy recovery during the braking – microprocessor-based – preventive and permanent diagnosis
<b>Drive battery type</b>	detachable battery pack in a single, AISI 316 steel container, composed of 14 6V lead-acid batteries with centralized topping up. 84 V 205A/h5h
<b>On-demand</b>	Battery pack with 14 lead-gel no-maintenance batteries - 84V 205A/h5h
<b>Battery charger</b>	Stand-alone (380V) – Optional: On board (220V)
<b>Recharge time</b>	6/8 hours
<b>Service battery</b>	12V 60Ah
<b>Interior compartment heating</b>	Independent 4kW Webasto burner, diesel
<b>Tyres</b>	155 R 12C 88N radial
<b>Brakes</b>	Front disc brakes – rear drum brakes Vacuum brake
<b>Turning diameter</b>	9,400 mm
<b>Top speed</b>	60 Km/h
<b>Gradeability</b>	18%
<b>Autonomy of operation</b>	75 Km
<b>Minimum height from the ground</b>	320 mm
<b>Maximum height from the ground</b>	1,780 mm
<b>Wheel base</b>	2,000 mm
<b>Maximum ground weight</b>	1,900 Kg
<b>Chassis empty weight</b>	1,140 Kg
<b>Chassis capacity</b>	760Kg
<b>Dimensions:</b>	
charging platform height	650 mm
length	3610 mm
width	1400 mm
height	1780 mm
rear overhang	790 mm